



SAFETY DATA SHEET SCENIX HIGH PERFORMANCE PAINT

1. Identification of the Preparation and of The Company

Product Name and/or code: Scenix High Performance Paint /
7500 Series Scenix High Performance Custom Paint
Effective Date: 9/29/17
Manufacturer: Color Craft Ltd/ Createx Colors
East Granby, CT 06026
Information Contact: 860-653-5505
860-653-5505
Emergency Contact: Contact your local Poison Control Center
Product Use: ART MATERIAL - Consumer Product

2. Hazards Identification

Emergency Overview *CAUTION! IRRITANT.*

Classification of the Product:

Label elements

Pictograms:

Conforms to ASTM D-4236



Signal Word

GHS07

CAUTION!

Hazard Statement

Causes eye, skin, nose and throat irritation. May cause sensitization.
Repeated skin contact may cause an allergic reaction.

Precaution Statement

Avoid contact with eyes, skin and clothing. Avoid breathing vapors or mist. Wash thoroughly after handling. **Use with adequate ventilation.**
Do not eat, drink or smoke when using this product. Avoid release to the environment.

First Aid Statement

In case of eye contact, flush immediately with plenty of water for at least 15 minutes and get medical attention immediately; for skin, wash thoroughly with soap and water. If you experience difficulty in breathing, leave the area to obtain fresh air.

Children's Statement

KEEP OUT OF THE REACH OF CHILDREN.

NFPA

Health: 1

Flammability: 0

Reactivity: 0

HMIS

Health: 1

Flammability: 0

Physical Hazard: 0

Regulation (EC) No. 1272/2008

This mixture is not classified as hazardous.



SAFETY DATA SHEET SCENIX HIGH PERFORMANCE PAINT

Export and Import of Dangerous
Chemicals Regulation (EC)No. 649/2012

This mixture is not classified as hazardous.

Directive 67/548/EEC &
Directive 1999/45/EC

This mixture is not classified as hazardous.

3. Composition/Information on Ingredients:

Substances:

Mixture of the following chemicals:

- Water (CAS No. 7732-18-5) < 50.00%
- 2- Butoxy ethanol (CAS No. 111-76-2) < 2.80%
- Propan-2-ol (CAS No. 67-63-0) < 0.40%
- BIT*: 1,2 -Benzisothiazol-3(2H)-one, 1,2- Benzisothiazolin-3-one (CAS No. 2634-33-5) < 7PPM

* The remainder of the formulation is composed of non-hazardous ingredients.

Risk and Safety Phrases:

Ingredients are marked according to CLP Regulation (CLP-Regulation (EC) No 1272/2008) and no workplace-related occupational exposure limits are specified for any of the listed ingredients. These ingredients are regarded as trade secrets.

4. First Aid Measures

Inhalation	If affected, remove to fresh air.
Skin Contact	Wash affected area thoroughly with plenty of soap and water.
Eye Contact	Carefully flush with water for 15 minutes and get medical attention immediately.
Ingestion	Drink water or milk to dilute. Do not induce vomiting. Contact a physician.

5. Firefighting Measures

Extinguishing Media	Water, foam, carbon dioxide or dry chemical equipment.
Fire/Explosion Hazards	This product is not known to present any fire hazard.
Flashpoint/Flammability	This product is not flammable.

6. Accidental Release Measures

Environmental precautions	Avoid release to the environment. <i>Studies have not been performed on this particular mixture.</i>
Methods and Materials for Containment and Cleaning up	Contain spill. Recover as much as possible. Absorb remainder with an inert material. Place into closed container and store in a safe location to await disposal. Wash the spill area with soap and water.



SAFETY DATA SHEET

SCENIX HIGH PERFORMANCE PAINT

7. Handling and Storage

Safe Handling: Use under ventilated conditions. Avoid eye contact and skin. For personal protection, we recommend that employees wash thoroughly after handling product. Always wash before eating, smoking or using toilet facilities. Keep container closed when not in use. Keep container upright to prevent leakage.

Storage Store between 50-100 deg. F., ideally 70 deg. F.

8. Exposure Controls / Personal Protection

Personal Protective Equipment Wear goggles where spills or splashing may occur. Wear water resistant impervious gloves if handling bulk amounts.

Exposure Limits

Substance	CAS#	OSHA PEL		NIOSH REL	ACGIH
		mg/m ³	8 hr. TWA(ST) STEL (C) Ceiling	Up to 10 - hr. TWA (ST) STEL (C) Ceiling	8 hr. TWA (ST) STEL (C) Ceiling
2-Butoxy ethanol	111-76-2	240	20 PPM	5 PPM	20 PPM
Propan-2-ol	67-63-0	980	400 PPM (ST) 500 PPM	400 PPM (ST) 500 PPM	200 PPM (ST) 500 PPM
1,2-Benzisothiazol-3(2H)-one, 1,2-benzisothiazolin-3-one	2634-33-5	NOT ESTABLISHED			

Respiratory and Ventilation Wear approved NIOSH/MSHA respirator if exposure to mist or vapor exceed applicable PEL/TLV limits. Use in accordance with manufacturer's use limitations and OSHA STANDARD 1910-34. Local ventilation may be used to prevent routine inhalation.

Skin Protection Wear water resistant impervious gloves if handling bulk amounts.

Eye Protection Wear goggles where spills or splashing may occur.

9. Physical and Chemical Properties

Appearance Colored paint

Physical State Liquid

VOC Content 38 g/L Regulatory

Solids percentage 27.82

Color See product list in Section 16

Odor Detergent-like

Boiling Point Not determined

Freezing Point Not determined

State (pH) 7.5-8.5

Specific Gravity 1.0 - 2.0

Viscosity 25 mPas

Flashpoint Greater than 200 °F

Vapor Pressure Not applicable



SAFETY DATA SHEET SCENIX HIGH PERFORMANCE PAINT

Vapor Density Not applicable
Solubility in water Miscible

10. Stability and Reactivity

Reactivity	Not reactive under conditions of normal use.
Chemical Stability	Stable under conditions of normal use.
Conditions to Avoid	All sources of ignition. Avoid heat. Avoid strong oxidizing agents.
Incompatible materials	Strong oxidizing agents, strong acids, strong bases, amines, ammonia, halogenated compounds
Hazardous Decomposition Products	Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapors.

11. Toxicological Information

Health Effects	Studies have not been performed on this particular mixture. The information below is based on data on the individual ingredients.
Oral	2-Butoxy ethanol: LD50 Rat: 300 - 2,000 mg/kg (literature value) 1-Methoxy-2-propanol: Expected to be greater than 2,000 mg/kg (Rats)
Dermal	2-Butoxy ethanol: LD50 Rabbit: >1,000 - 2,000 mg/kg (literature value) 1-Methoxy-2-propanol: No data available. BIT: No data available. MIT: No data available. CIT: No data available.
Inhalation	Triethylamine: LD50 Rabbit: 416 mg/kg 2-Butoxy ethanol: LC50 (4h) Rat: 10 - 20 mg/l (literature value) 1-Methoxy-2-propanol: No data available. BIT: No data available. MIT: No data available. CIT: No data available. Triethylamine: LC50 (4h) Rat: 4.2 mg/l
Eye Effects	Causes eye irritation.
Dermal Effects	Causes skin irritation. Repeated skin contact may cause an allergic reaction.
Sensitization Effects	May cause sensitization.
Inhalation Effects	Causes nose and throat irritation.
Ingestion Effects	None known for the usual and ordinary uses of this product.
<u>Additional Toxicological Information:</u>	<i>When used and handled according to specifications, the product does not have any harmful effects according to past experience and the information provided by the manufacturer.</i>

12. Ecological Information

Toxicity:	Not expected to be harmful to the environment. Studies have not been performed on this particular mixture.
-----------	--



SAFETY DATA SHEET SCENIX HIGH PERFORMANCE PAINT

Aquatic toxicity	BIT: 1,2 -Benzisothiazol-3(2H)-one, 1,2- benzisothiazolin-3-one is a substance known to be very toxic to aquatic life.
Persistence and degradability	No information available.
Bio accumulative potential	No information available.
Mobility in soil	No information available.
Additional ecological information	No information available.

13. Disposal Considerations

Dispose of all waste material in accordance with all applicable federal, state and local regulations for the disposal of aqueous polymer wastes.

14. Transportation Information

DOT Non-Bulk	This regulation does not apply to the non-bulk material.
Shipping Name	Not regulated.
Technical Shipping Name	Not regulated.
Hazard Class	Not regulated.
UN Number	Not regulated.
Packing Group	Not regulated.
IMDG	This regulation does not apply to the non-bulk material.
Shipping Name	Not regulated.
Technical Shipping Name	Not regulated.
Hazard Class	Not regulated.
UN Number	Not regulated.
Packing Group	Not regulated.
EmS Number	Not regulated.
Marine Pollutant	Not regulated.
ICAO/IATA	This regulation does not apply to the non-bulk material.
Shipping Name	Not regulated.
Technical Shipping Name	Not regulated.
Hazard Class	Not regulated.
UN Number	Not regulated.
Packing Group	Not regulated.
Marine Pollutant	Not regulated.

This information is not intended to convey all specific regulatory or operational requirements/information relating to this product. It is the responsibility of the transporting organization to follow all applicable laws, regulations and rules relating to the transportation of the materials.

15. Regulatory Information

Safety, health and environmental regulations/legislation specific for the substance or mixture.

SARA Not applicable to this mixture.



SAFETY DATA SHEET SCENIX HIGH PERFORMANCE PAINT

Section 355 (extremely hazardous substances) Not applicable to this mixture.

Section 313 (Specific toxic chemical listing) Not applicable to this mixture.

TSCA (Toxic Substance Control Act): All ingredients are listed.

Proposition 65 WARNING: Cancer - www.P65Warnings.ca.gov

As of September 15, 2017, this product contains listed substances known to the State of California to cause cancer, at levels which would require a warning under the statute.

Carcinogenicity Categories:

EPA (Environmental Protection Agency) Not applicable to this mixture.

TLV (Threshold Limit Value established by ACGIH) Refer to section 8.

MAK (German Maximum Workplace Concentration): Not applicable to this mixture.

NOISH-Ca (National Institute for Occupational Safety & Health): Not applicable to this mixture.

OSHA-Ca (Occupational Safety & Health Administration): Not applicable to this mixture.

16. Other Information

COLOR INFORMATION

Product	SKU	Hazardous Ingredient
Scenix High Performance Paint / 7500 Series Scenix High Performance Custom Paint		(None)

Original Date:	New Product
Reason for Issue:	Updated formula information
Prepared by:	Rudolph J. Jaeger, Ph.D., DABT, ERT (UK) Chief Toxicologist and President ENVIRONMENTAL MEDICINE, INC. 263 CENTER AVENUE WESTWOOD, NJ 07675 jaegerr@envmed.com 201-666-7929 x13

The information contained in this Safety Data Sheet was compiled using the latest and most reliable information available to Color Craft Ltd./ Createx Color. The information is provided without any warranty, express or implied



SAFETY DATA SHEET SCENIX HIGH PERFORMANCE PAINT

regarding its correctness or accuracy nor will Color Craft Ltd./ Createx Color. assume any liability for any loss or damage arising out of the use of this information including without limitation direct or indirect losses or expenses. To the extent permitted by law, no warranty express or implied regarding the product described herein shall be created by or inferred from any state or omission for this SDS. It is solely the responsibility of the user to determine safe conditions for use of this product and to assume liability for any loss, damage or expense whatsoever arising out of the product's improper use.

Abbreviations and acronyms:

NFPA (SCALE 0-4) National Fire Protection Association (USA)

Health: 1	Caution: May be irritating.
Fire: 0	Not combustible.
Reactivity: 0	Not reactive when mixed with water.

HMIS (SCALE 0-4) Hazardous Materials Identification System (USA)

Health: 1	Irritation or minor reversible injury possible.
Fire: 0	Materials that will not burn.
Reactivity: 0	Materials that are normally stable, even under fire conditions, and will NOT react with water, polymerize, decompose, condense, or self- react. Non-Explosives.

H Statements

H225 - Highly Flammable liquid and vapour.
H226 - Flammable liquid and vapour.
H302 - Harmful if swallowed.
H312 - Harmful in contact with skin.
H314 - Causes severe skin burns and eye damage.
H315 - Causes skin irritation.
H317 - May cause an allergic reaction.
H318 - Causes serious eye damage.
H319 - Causes serious eye irritation.
H332 - Harmful if inhaled.
H336 - May cause drowsiness or dizziness.
H400 - Very Toxic to aquatic life.

Exposure Limits

TWA - Time Weighted Average (8 hr.)
STEL - Short Time Exposure Limit (15 min.)
REL - Recommended Exposure Limit
PEL - Permissible Exposure Limit
IDLH - Immediately Dangerous to Life or Health